

If you have any comments or concerns,
please feel free to contact our
customer service department at:
Toll-free: 1-800-835-0438
OR
Email: info@gofia.com

HEAVY-DUTY TRUCK
SEAT COVERS
BY



FEATURING

SUPER-GRIP®


THE SLIP RESISTANT FASTENING SYSTEM

INSTALLATION INSTRUCTIONS
FOR
Oe3024/ SP8024/ TR4024/TRS4024



Thank you for purchasing one of our fine quality products. Your seat cover is engineered from high quality materials and designed with precision to give you a long-lasting, well-adjusted fit.

The **Super Grip Buckles** are self-locking. For proper usage, see diagram:



BACKREST:

- 1) Move seat to most forward position
- 2) Slip cover over backrest – pull down firmly
- 3) Smooth tightly from top to bottom of backrest
- 4) Tuck flap through crevice and attach to Velcro at back

NOTE: FOR SEATS WITH ARMRESTS – THE BACKREST PORTION OF THE SEAT COVER HAS VELCRO CLOSURES ON THE SIDE OF COVER TO ALLOW FOR FITTING AROUND ARMRESTS.

CUSHION:

- 1) Center cover over seat cushion
- 2) Lift cushion to up position
- 3) Pass front strap under seat and buckle to back strap
- 4) Pass side straps across the seat and buckle
- 5) Adjust all straps/buckles to equalize tension for a uniform fit

WASHING INSTRUCTIONS:

Hand wash using mild detergent and COLD WATER. Always drip dry. DO NOT DRY CLEAN.

WARNING:

NEVER INSTALL SEAT COVERS ON SEATS WITH BUILT-IN AIRBAGS AS THIS MAY INTERFERE WITH THE PROPER DEPLOYMENT OF THE AIRBAGS.



Fia Inc. Winnipeg, Canada Telephone: (204) 475-0515 Toll-Free: 1-800-835-0438
Fax: (204) 284-8246 E-Mail: info@gofia.com Website: www.gofia.com

8-18-10