

## Technical Data Sheet

### General

Article number: 4010, 4020, 4030  
Description: Colad Undercoating M80



### Specification

- In contrast of the usual bitumen/caoutchouc material, Colad Undercoating has extremely high abrasion resistance and can be over lacquered if required.
- Available
  - Art. no. 4010 - Colad Undercoating M80 black
  - Art. no. 4020 - Colad Undercoating M80 white
  - Art. no. 4030 - Colad Undercoating M80 gray
- Colad Undercoating M 80 can be recoated without bleeding.
- Packing: in 1 liter tins with spray connection.
- Packing unit: in box of 12 x 1 liter.
- Shelf life: 2 years (storage between 10 and 20° C).

### Remarks

- A noise absorbing Undercoating for motor bodies.
- Protects against corrosion and salt, is flexible and chip resistant.
- Removal: Colad Undercoating M80 can be removed with mineral spirits.

#### Special remarks:

As with all materials based on synthetic resins, this undercoating needs several days to reach maximum hardness. However, after 30 minutes the film can be painted over with all types of automobile lacquers.

### Created by :

E.M.M. International BV  
Marsweg 59  
8013 PE Zwolle  
The Netherlands

phone +31 38 4676600  
fax +31 38 4676699  
[www.emm.com](http://www.emm.com)