

# **INSTALLATION MANUAL**

45902

## **Level of Difficulty**

Easy

#### Weight Capacity: 2" Ball

Gross trailer weight (GTW) 10,

10,000 lbs.

## Weight Capacity: 2-5/16" Ball

Gross trailer weight (GTW) 20,000 lbs.

#### **Parts List**

1	Channel mount
1	Dual ball
1	Channel pin
1	Channel clip
1	Hitch pin & clip

## Step 1

Insert the adjustable channel mount into the vehicle's trailer hitch receiver tube and secure with the provided hitch pin & clip or hitch lock (hitch lock sold separately).

# Step 2

Determine the tow height needed for your towing situation. Position the dual ball and insert the provided channel pins through the channel mount and dual ball. Secure the pins with the provided channel clips.

#### **⚠ WARNING**

The provided pins are specifically engineered for this system. If replacement pins are needed, they must be replaced with original factory mount pins.

#### **⚠ WARNING**

Never exceed the vehicle manufacturer's recommended towing capacity. The ratings of the channel-mount system are intended to represent the capability of the product and in no way reflect the ratings or capacity of the towing system it is being used with. The consumer or operator are strongly advised to know the ratings of the various components of the towing system and never exceed the limits of the lowest rated component being used.

Use of any pin other than what is provided by the manufacturer could be a serious safety hazard and will void the warranty.

Never hook up trailer safety chains to the mount system. Ensure the safety chains operate freely around the mount system and do not become entangled.

#### **Product Photo**



## NOTICE

Before you begin installation, read all instructions thoroughly.

Proper tools will improve the quality of installation and reduce the time required.

#### **Product Registration and Warranty**

CURT Group stands behind our products with industry-leading warranties.

Provide feedback and help us to improve our products by registering your purchase at: warranty.curtgroup.com/surveys

