

Rancher Grille Guard

Installation Instructions

44650 / 46650

Ford F-150 2015 - 2017




Diagram 1

Parts List:

1-Grille Guard	8- 1/2"-13 Hex nuts
1-Driver Side Upper Bkt #46650-5	8 - 1/2" x 1 1/2" Bolts
1-Pass. Side Upper Bkt #46650-6	16 - 1/2" Flat Washers
1-Driver Side Lower Bkt #46650-7	8 - 1/2" Lock Washers
1-Pass. Side Lower Bkt #46650-8	—

***May include extra hardware.**

Note: Completely read instructions before beginning installation!

1. Remove the contents from the box and check for missing pieces or damage. If parts are missing or damaged, contact the original place of purchase.
2. If vehicle comes equipped with factory tow hooks. The factory tow hooks will have to be removed. The tow hooks will not be reused. The brackets are equipped with holes to be used as the tow hooks.
3. Remove plastic finish panel in the center of the factory bumper by squeezing clips from behind bumper, then pushing outward. Unplug fog lamps, if equipped, then remove rear bumper nuts. In the front, remove the two bumper nuts on each side and remove bumper. (**see diagram 2**)
4. Reuse the factory nut plate in the frame and line up the 2 holes on the bottom of the frame with the holes on the nut plate. It is recommended to use tape to hold the nut plate in place because access will be limited later. Do not install lower brackets at this time. Reinstall factory upper bolt plates and hang the upper brackets #46650-5 (driver's) #46650-6 (passenger) on the bolt plate against the frame. (**see diagram-3**) Reinstall the front bumper, sandwiching the upper bracket between the frame and the bumper. Reinstall the factory bumper nuts but do not tighten at this time.
5. Install the lower brackets #46650-8 and #46650-9 to the frame where the tow hooks were removed. Thread the factory tow hook bolts through the lower brackets into the previously installed nut plate. (Hint: install the rear bolts first) (**see diagram-4 & 5**)
6. Place (1) 1/2" flat washer on to each of the (8) 1/2" x 1 1/2" bolts. Using the (8) bolts with washers attach the grille guard to the brackets with (8) 1/2" flat washers, (8) 1/2" lock washers and (8) 1/2"-13 hex nuts. Hand tighten all bolts at this time.
7. While centering the grille guard on the vehicle, tighten the lower bracket to frame bolts. Then tighten all six factory bumper bolts and plug in fog lamps. There will not be any up and down adjustment in the bumper.
8. Remove the bolts connecting the upper bracket to the grille guard and one set of lower bracket bolts. Carefully tilt the grille guard forward and reinstall the plastic filler in the center of the bumper. Reinstall the bracket bolts and tighten all bolts.

Rancher Grille Guard

Installation Instructions

44650 / 46650

Ford F-150 2015 - 2017

View of Bumper on Vehicle Without Plastic filler



Diagram 2

Driver Side upper bracket # 46650-5




Diagram 3

Underside View of Driver Bracket #46650-7



Diagram 4

View of Driver Side Bracket #46650-7 with bumper



Diagram 5