Revision Date: 9/27/2019

Section 1. Product and Company Identification

Product Identifier K24 - Tree Sap Remover

Product Use Description:

Clear thin liquid with an alcohol odor - for use as a tree sap remover on automotive

surfaces.

Manufacturer or suppliers' details

P & S Sales, Inc Emergency Number: 800-255-3924 20943 Cabot Blvd. Customer Service: 510-732-2628 Hayward CA 94545 Business Fax: 510-732-2632

Section 2. Hazards Identification

GHS Classification

Flammable Liquids: Category 2

Eye Irritation: Category 2A

Specific target organ toxicity - single exposure: Category 3 (Central nervous system)

GHS Label Elements

Hazard Pictograms





Hazard Word Danger

Hazard Statements

Highly flammable liquid and vapour

Causes serious eye irritation May cause respiratory irritation May cause drowsiness or dizziness

Precautionary Statements

P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking

P233: Keep container tightly closed

P261: Avoid breathing dust/fume/gas/mist/vapours/spray

P264: Wash skin thoroughly after handling

P271: Use only outdoors or in a well-ventilated area

P280: Wear protective gloves/protective clothing/eye protection/face protection

P303+361+353: Response:

P304+340: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

P312: skin with water/shower

P305+351+338: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

P337+313: breathing

P370+378: Call a POISON CENTER or doctor/physician if you feel unwell

P403+235: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if

present and easy to do - continue rinsing

Revision Date: 9/27/2019

P501: If eye irritation persists get medical advice/attention ACGIH

In case of fire: Use dry sand, dry chemical or alcohol resistant foam for extinction

OSHA Storage:

NTP Store in a well ventilated place. Keep cool IARC

Dispose of contents/container to an approved waste disposal plant.

Carcinogenicity:

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

3. Composition Information on Ingredients

CAS Number	Wt %	Component Name
64-17-5	30-40%	Ethanol
109-60-4	2-4%	Propyl Acetate
67-63-0	1-2%	Isopropanol, 2-Propanol
29911-28-2	15-25%	2-Propanol, 1-(2-butoxy-1-methylethoxy)-

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion: Give large amounts of water to drink. Never give anything by mouth to an unconscious person. Get medical attention.

Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes. Call a physician if irritation develops.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Suitable extinguishing media: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical

Unsuitable extinguishing media: High volume water jet

Specific hazards during firefighting: Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products: Carbon oxides

Specific extinguishing methods: Use a water spray to cool fully closed containers.

Further information: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.

Page :

Revision Date: 9/27/2019

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

7. Handling and Storage

Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Small quantities of peroxides can form on prolonged storage. Exposure to light and/or air significantly increases the rate of peroxide formation. If evaporated to a residue, the mixture of peroxides and isopropanol may explode when exposed to heat or shock.

8. Exposure Controls and Personal Protection

64-17-5 Ethanol	1000 ppm NIOSH REL TWA
	1000 ppm OSHA 7-1 TWA
109-60-4 Propyl Acetate	200 ppm ACGIH TWA
	200 ppm OSHA Z-1 TWA
	250 ppm OSHA P0 STEL
	1050 mg/m3
67-63-0 Isopropanol, 2-Propanol	
·	400 ppm STEL ACGIH
	500 ppm OSHA P0 STEL
	1225 mg/m3
29911-28-2 2-Propanol, 1-(2-butoxy-1-methyletho	xy)- None Established

VENTILATION

Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. No smoking, or use of flame or other ignition sources.

Revision Date: 9/27/2019

RESPIRATORY PROTECTION

Use supplied-air respiratory protection in confined or enclosed spaces, if needed.

PROTECTIVE GLOVES

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION

Use splash goggles or face shield when eye contact may occur.

OTHER PROTECTIVE EQUIPMENT

Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing, which could result in prolonged or repeated skin contact.

WORK PRACTICES / ENGINEERING CONTROLS

To prevent fire or explosion risk from static accumulation and discharge, effectively bond and/or ground product transfer system in accordance with (THE) National Fire Protection Association PUBLICATIONS.

9. Physical and Chemical Properties

Flash Point 26°C (79°F) Upper Flamability Limit 12.7 % Auto Ignition 399°C (750°F) Lower Flamability Limit 2.0 %

Physical State liquid Color Green Vapor Press 44 mmHq

pH 5.5 Specific Gravity .906 Viscosity thin

Vapor Density (Air=1) 2.1 Melting Point °F -11°F Odor alcohol

Water Solubility complete VOC Content 59% for CARB VOC see Section 15

10. Stability and Reactivity

Stability Stable Hazardous Polymerization Not Expected to Occur

Conditions to Avoid Keep away from extreme heat, Strong Acids, Alkalies and Oxidizers such as

Chlorine, other Halogens, Hydrogen Peroxide and Oxygen

Hazardous No substances are readily identifiable from composition but no degradation

Decomposition Products data is available.

11. Toxicological Information

Product:

Acute oral toxicity: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity: Acute toxicity estimate: > 125 mg/l Exposure time: 4 h, Test atmosphere: vapour
Acute dermal toxicity: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method

12. Ecological Information

K24 - Tree Sap Remover

Page 5

Revision Date: 9/27/2019

Environmental Fate:

When released into the soil, this material is expected to quickly evaporate, may leach into groundwater and may biodegrade to a moderate extent. When released to water, this material is expected to quickly evaporate, have a half-life between 1 and 10 days and may biodegrade to a moderate extent. This material is not expected to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals, to have a half-life between 1 and 10 days and may be removed from the atmosphere to a moderate extent by wet deposition.

Environmental Toxicity: The LC50/96-hour values for fish are over 100 mg/l. This material is not expected to be toxic to aquatic life.

13. Disposal Considerations

Options for disposal of this product may depend on the conditions under which it was used. To determine the proper method of disposal, refer to RCRA (40 CFR 261), as well as federal EPA and state and local regulations.

Please refer to Sections 5, 6 and 15 for additional information.

14. Transportation Information

Domestic (Land, D.O.T.)

Proper Shipping Name: UN1993, Flammable Liquid, N.O.S. (Ethanol), PG II

Information reported for product/size: 32 oz up to 55 gallon drum.

For packages not over 1 Liter: Limited quantity exemption 49 CFR 173.150(b)(2)

International (Water, I.M.O.)

Proper Shipping Name: UN1993, Flammable Liquid, N.O.S. (Ethanol), PG II

Information reported for product/size: 32 oz up to 55 gallon drum.

15. Regulatory Information

OSHA Hazards: Flammable Liquid, Moderate eye irritant, Moderate respiratory irritant

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity - This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards: Fire Hazard, Acute Health Hazard

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313: SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Revision Date: 9/27/2019

California Prop. 65: This product can expose you to chemicals including acetaldehyde, which is known to the state of California to cause cancer. For more information go to www.p65warnings.ca.gov

CARB VOC info: 39% VOC as regulated by CARB Consumer Products requirements, LVP-VOC

exception

ARB VOC Info: 1.3 lb/gal VOC; 155.8 g/L

16. Other Information Revision Date 9/27/2019

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH American Conference of Government Industrial Hygienists

LD50 Lethal Dose 50%

AICS Australia, Inventory of Chemical Substances

LOAEL Lowest Observed Adverse Effect Level

DSL Canada, Domestic Sub- stances List

NFPA National Fire Protection Agency

NDSL Canada, Non-Domestic Sub- stances List

NIOSH National Institute for Occupational Safety & Health

CNS Central Nervous System

NTP National Toxicology Program

CAS Chemical Abstract Service

NZIoC New Zealand Inventory of Chemicals

EC50 Effective Concentration

NOAEL No Observable Adverse Effect Level

EC50 Effective Concentration 50%

NOEC No Observed Effect Concentration

EGEST EOSCA Generic Exposure Scenario Tool

OSHA Occupational Safety & Health Administration

EOSCA European Oilfield Specialty Chemicals Association

PEL Permissible Exposure Limit

EINECS European Inventory of Exist- ing Chemical Substances

PICCS Philipines Inventory of Commercial Chemical Substances

MAK Germany Maximum Concentration Values

PRNT Presumed Not Toxic

GHS Globally Harmonized System

RCRA Resource Conservation Recovery Act

>= Greater Than or Equal To

STEL Short-term Exposure Limit

IC50 Inhibition Concentration 50%

SARA Superfund Amendments and Reauthorization Act.

IARC International Agency for Re- search on Cancer

TLV Threshold Limit Value

IECSC Inventory of Existing Chemical Substances in China