## INSTALLATION INSTRUCTIONS AND PARTS LIST

APPLICATION: MODEL 200232 STAINLESS STEEL SIDE ENTRY STEPS ON: 2002 AND NEWER DODGE RAM QUAD CAB PICKUPS

- 1. READ INSTRUCTIONS COMPLETELY AND CHECK TO MAKE SURE THAT ALL REQUIRED PARTS (LISTED ON SERVICE PARTS LIST) ARE ON HAND BEFORE STARTING THE INSTALLATION.
- 2. PEEL AWAY THE PROTECTIVE VINYL COVERING AND CLEAN THE TOP OF EACH STEP PLATE TO REMOVE ANY VINYL COVERING RESIDUE. (A GOOD GLASS CLEANER IS SUGGESTED).
- 3. THE STEP ASSEMBLIES MUST BE MOUNTED TO THE PINCH WELD AND INBOARD VERTICAL SURFACE OF THE ROCKER PANEL PER THE FOLLOWING INSTRUCTIONS.
  - 3.1. FROM FRONT TO REAR, REMOVE RUBBER PLUGS FROM THE #4, #6 & #8 ACCESS HOLES ON THE INBOARD VERTICAL WALL OF THE ROCKER PANEL.
  - 3.2. POSITION THE STEP ASSEMBLY (ITEM #1 THRU #11) UP UNDER THE ROCKER PANEL SO THAT THE FRONT END CAP IS JUST BEHIND THE HEAD OF THE FACTORY BOLT ON THE BOTTOM OF THE ROCKER PANEL.
  - 3.3. PUSH THE STEP ASSEMBLY SNUG UP UNDER THE ROCKER PANEL, LEVEL THE STEP PLATE AND CLAMP THE BRACES (ITEM #3) TO THE PINCH WELD.
  - 3.4. MARK THE CENTER OF THE BRACE'S BOTTOM HOLES ON THE PINCH WELD AND THEN DRILL PILOT HOLES AND 17/64" DIA. HOLES THRU THE PINCH WELD. (LOCATE THESE HOLES AS CLOSE TO CENTER AS IS PRACTICAL ON THE FLAT PORTION OF THE PINCH WELD).
  - 3.5. INSTALL 5/16" X 3/4" HEX WASHER HEAD THREAD FORMING SCREWS (ITEM #12). (TORQUE THESE SCREWS TO 15 LB. FT.).
  - 3.6. USING ONE OF THE UPPER HOLES (AS SHOWN) IN THE BRACE AS A PILOT, DRILL PILOT HOLES AND 17/64" DIA. HOLES THRU THE VERTICAL WALL OF THE ROCKER PANEL.
  - 3.7. INSTALL 5/16" X 3/4" HEX WASHER HEAD THREAD FORMING SCREWS (ITEM #12) AS SHOWN. (BEING CAREFUL NOT TO OVER TIGHTEN, TORQUE THESE SCREWS TO APPROX. 10 LB. FT.).

## SERVICE PARTS LIST

ITEM	PART NO.	QTY	DESCRIPTION
1	550965	1	STEP PLATE-SES,RH,DODGE RAM,QUAD CAB
2	550967	1	STEP PLATE-SES,LH,DODGE RAM,QUAD CAB
3	550958	8	BRACE-SUPPORT,SES,RH/LH,DODGE RAM
4	104250	2	END CAP-RH FRONT/LH REAR
5	104251	2	END CAP-LH FRONT/RH REAR
6	102600	4	PAD,STEP PLATE,20.00"
7	104255	2	TRIM-SEAL,SES,EXTRUDED
8	104257	12	NUT-HEX,SGL SELF THD,CAP WASHER,1/4"
9	104258	8	BOLT-CARRIAGE,SST,#10-24 X 3/4"LG
10	104259	8	BOLT-CARRIAGE,CLP HD,SST,#10-24 X 3/4"LG
11	104261	16	NUT-SERRATED FLANGE,HEX,SST,#10-24
12	104267	24	SCREW-HEX HD,THD FORMING,AB,5/16" X 3/4"
	_		

