If you have any comments or concerns, please feel free to contact our customer service department at:

Toll-free: 1-800-835-0438

OR

Email: info@gofia.com

SEAT COVERS





# THE SLIP RESISTANT FASTENING SYSTEM

## INSTALLATION INSTRUCTIONS FOR

NP98-15/ Oe38-15/ SL68-15/ SP88-15/ TR48-15/ TRS48-15

Thank you for purchasing one of our fine quality products. Your seat cover is engineered from high quality materials and designed with precision to give you a long-lasting, well-adjusted fit.

- 1) Remove head rest (see note)
- 2) Open zipper
- 3) Slip cover over backrest under seat belt
- 4) Close zipper (see note)
- 1) Center cover on the seat
- 2) Pass the front strap under seat and buckle to back flap

#### A) BACKREST COVER

- 5) Tuck flaps under backrest and attach to Velcro at back
- 6) Adjust Velcro to equalize tension
- 7) Replace headrests (see note)

### B) CUSHION COVER

- 3) Pass side straps around back of seat and buckle
- 4) Adjust straps and buckles to equalize tension

#### NOTES:

1) SELF-LOCKING SUPER-GRIP® BUCKLE:



## 2) HEAD REST REMOVAL:

- A) Insert paper clip into holes at base to release
  - Lift off

#### OR

- B) Push in side release buttons
- Lift off

(If unable to remove consult dealership)



## 3) SEATS WITH SIDE ARMRESTS:

- Locate opening in stretch fabric
- Slip armrest through opening

#### 4) ZIPPERS:

- For ease in installation the zipper is longer than the cover.
- Tuck excess zipper under cover

## 5) RE-INSTALLATION OF HEADRESTS

- A) Ensure pre-cut holes in seat cover align with holes in base.
- B) Replace headrests

WARNING: SEATS WITH INTEGRATED SEAT AIRBAGS MUST BE COVERED ONLY WITH SEATCOVERS DESIGNED WITH OPENINGS THAT WILL NOT INTERFERE WITH THE DEPLOYMENT OF THE AIRBAG.. NEVER INSTALL SEAT COVERS WITHOUT THESE OPENINGS AS THIS MAY INTERFERE WITH THE PROPER DEPLOYMENT OF THE AIR BAGS AND COULD RESULT IN SERIOUS INJURY.

fia

Fia Inc. Winnipeg, Canada R3L 0N3 Telephone (204) 475-0515 Toll-Free: 1-800-835-0438 Fax: (204) 284-8246 E-Mail: info@gofia.com Website: www.gofia.com