

Auto Magic

Professional Car Care

SOLVENTS & REMOVERS

Iron Clear™

Color-Changing Iron & Fallout Remover
Identifies and Easily Removes Iron Particles,
Brake Dust, & Embedded Contaminants

VOC COMPLIANT
BODYSHOP SAFE

PRECAUTIONS ON SIDE PANEL

No. **42**

Container Intended for #42 Iron Clear™ Only

No. 42 Iron Clear

Iron Clear™ Color Changing Fallout Remover is a pH balanced, color changing fallout remover designed for safe removal of iron particles, brake dust, and contaminants commonly found embedded on vehicles surfaces such as wheels, body panels, painted bumper covers and moldings. This fast-acting formula has a pleasant lemon scent and color changing properties (from green to red/purple) that show the effectiveness of contaminant identification and removal. The formula is designed to spray easily yet have excellent cling and clean properties. **DIRECTIONS:** Iron Clear, Color Changing Fallout Remover is RTU. Allow surfaces, such as wheels and painted surfaces to cool. Never spray on a hot black surface. Wash and rinse vehicle, some additional water left on the surface does not impact performance. Shake bottle well, then spray enough to evenly coat contaminated surfaces. Allow to dwell 2-4 minutes and rinse thoroughly making sure all Iron Clear, Color Changing Fallout Remover is removed. Do not allow chemical to dry on any surfaces. **Helpful Tip:** Avoid use on parts that are painted with spray cans or low-quality paints. Examples: Brake calipers, or unknown wheel coatings.



DANGER - May cause an allergic skin reaction. May cause cancer. Flammable liquid and vapor. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use non-sparking tools. Take precautionary measures against static discharge. **FIRST AID:** If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: Use CO2, dry chemical, or foam to extinguish. Store locked up. Store in a well-ventilated place. Keep cool. Dispose of contents/container to an approved waste disposal plant. See Safety Data Sheet for additional information.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
DANGER - Peut provoquer une allergie cutanée. Peut provoquer le cancer. Liquide et vapeurs inflammables. Se procurer les instructions avant l'utilisation. Ne pas manipuler avant d'avoir lu et compris toutes les précautions de sécurité. Utiliser l'équipement de protection individuelle requis. Éviter de respirer les poussières/fumées/gaz/brouillards/vapeurs/aérosols. Les vêtements de travail contaminés ne devraient pas sortir du lieu de travail. Porter des gants de protection. Tenir à l'écart de la chaleur/des étincelles/des flammes nues/des surfaces chaudes. Ne pas fumer. Maintenir le récipient fermé de manière étanche. Mise à la terre/liaison équipotentielle du récipient et du matériel de réception. Utiliser du matériel électrique / de ventilation / d'éclairage antidéflagrant. Utiliser des outils ne produisant pas des étincelles. Prendre des mesures de précaution contre les décharges électrostatiques. **PREMIERS SOINS:** EN CAS d'exposition prouvée ou suspectée: consulter un médecin. En cas d'irritation ou d'éruption cutanée: consulter un médecin. Laver les vêtements contaminés avant réutilisation. EN CAS DE CONTACT AVEC LA PEAU (ou les cheveux): enlever immédiatement les vêtements contaminés. Rincer à l'eau/se doucher. En cas d'incendie: Utiliser du CO2, une poudre extinctrice ou une mousse pour l'extinction. Garder sous clef. Stocker dans un endroit bien ventilé. Tenir au frais. Éliminer le contenu/récipient dans une usine d'élimination des déchets approuvée. Voir la fiche de sécurité pour plus d'information.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov

Contains (CAS#): DI WATER (7789-20-0), Sodium Mercaptoacetate (367-51-1), Sodium Laureth Sulfate (9004-82-4), Water (7732-18-5), Ethanol (64-17-5), Proprietary Emulsifier (PROPRIETARY), Sodium Xylene Sulfonate (1300-72-7), N,N-Dimethyl 9-decanamide (1356964-77-6), ALCOHOLS, C12-15, ETHOXYLATED (68131-39-5), (d)-limonene (5989-27-5), Soda Ash (Sodium Carbonate) (497-19-8), Sodium Sulfate (7757-82-6). Contains fragrance allergen(s). For more ingredient information visit www.automagic.com or call toll-free 1-800-729-7600.

LIMITATION OF LIABILITY: Auto Magic® Distributors and/or ITW agents will not be liable for any loss or damage arising from this product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. Auto Magic® products should always be used as directed.

Auto Magic
Professional Car Care

FOR PROFESSIONAL USE ONLY

Manufactured in USA of foreign and US components
Auto Magic is a trademark of ITW Evercoat
a division of Illinois Tool Works Inc.
6600 Cornell Rd, Cincinnati, OH 45242
513-489-7600 | AutoMagic.com

ITW Permatex Canada
a division of Illinois Tool Works Inc.
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5

187444 6.2020

Auto Magic

Professional Car Care

SOLVENTS & REMOVERS

Iron Clear™

Color-Changing Iron & Fallout Remover
Identifies and Easily Removes Iron Particles,
Brake Dust, & Embedded Contaminants

VOC COMPLIANT
BODYSHOP SAFE

PRECAUTIONS ON SIDE PANEL

No. **42**

Container Intended for #42 Iron Clear™ Only

No. 42 Iron Clear

Iron Clear™ Color Changing Fallout Remover is a pH balanced, color changing fallout remover designed for safe removal of iron particles, brake dust, and contaminants commonly found embedded on vehicles surfaces such as wheels, body panels, painted bumper covers and moldings. This fast-acting formula has a pleasant lemon scent and color changing properties (from green to red/purple) that show the effectiveness of contaminant identification and removal. The formula is designed to spray easily yet have excellent cling and clean properties. **DIRECTIONS:** Iron Clear, Color Changing Fallout Remover is RTU. Allow surfaces, such as wheels and painted surfaces to cool. Never spray on a hot black surface. Wash and rinse vehicle, some additional water left on the surface does not impact performance. Shake bottle well, then spray enough to evenly coat contaminated surfaces. Allow to dwell 2-4 minutes and rinse thoroughly making sure all Iron Clear, Color Changing Fallout Remover is removed. Do not allow chemical to dry on any surfaces. **Helpful Tip:** Avoid use on parts that are painted with spray cans or low-quality paints. Examples: Brake calipers, or unknown wheel coatings.



DANGER - May cause an allergic skin reaction. May cause cancer. Flammable liquid and vapor. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use non-sparking tools. Take precautionary measures against static discharge. **FIRST AID:** If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: Use CO2, dry chemical, or foam to extinguish. Store locked up. Store in a well-ventilated place. Keep cool. Dispose of contents/container to an approved waste disposal plant. See Safety Data Sheet for additional information.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
DANGER - Peut provoquer une allergie cutanée. Peut provoquer le cancer. Liquide et vapeurs inflammables. Se procurer les instructions avant l'utilisation. Ne pas manipuler avant d'avoir lu et compris toutes les précautions de sécurité. Utiliser l'équipement de protection individuelle requis. Éviter de respirer les poussières/fumées/gaz/brouillards/vapeurs/aérosols. Les vêtements de travail contaminés ne devraient pas sortir du lieu de travail. Porter des gants de protection. Tenir à l'écart de la chaleur/des étincelles/des flammes nues/des surfaces chaudes. Ne pas fumer. Maintenir le récipient fermé de manière étanche. Mise à la terre/liaison équipotentielle du récipient et du matériel de réception. Utiliser du matériel électrique / de ventilation / d'éclairage antidéflagrant. Utiliser des outils ne produisant pas des étincelles. Prendre des mesures de précaution contre les décharges électrostatiques. **PREMIERS SOINS:** EN CAS d'exposition prouvée ou suspectée: consulter un médecin. En cas d'irritation ou d'éruption cutanée: consulter un médecin. Laver les vêtements contaminés avant réutilisation. EN CAS DE CONTACT AVEC LA PEAU (ou les cheveux): enlever immédiatement les vêtements contaminés. Rincer à l'eau/se doucher. En cas d'incendie: Utiliser du CO2, une poudre extinctrice ou une mousse pour l'extinction. Garder sous clef. Stocker dans un endroit bien ventilé. Tenir au frais. Éliminer le contenu/récipient dans une usine d'élimination des déchets approuvée. Voir la fiche de sécurité pour plus d'information.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov

Contains (CAS#): DI WATER (7789-20-0), Sodium Mercaptoacetate (367-51-1), Sodium Laureth Sulfate (9004-82-4), Water (7732-18-5), Ethanol (64-17-5), Proprietary Emulsifier (PROPRIETARY), Sodium Xylene Sulfonate (1300-72-7), N,N-Dimethyl 9-decanamide (1356964-77-6), ALCOHOLS, C12-15, ETHOXYLATED (68131-39-5), (d)-limonene (5989-27-5), Soda Ash (Sodium Carbonate) (497-19-8), Sodium Sulfate (7757-82-6). Contains fragrance allergen(s). For more ingredient information visit www.automagic.com or call toll-free 1-800-729-7600.

LIMITATION OF LIABILITY: Auto Magic® Distributors and/or ITW agents will not be liable for any loss or damage arising from this product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. Auto Magic® products should always be used as directed.

Auto Magic
Professional Car Care

FOR PROFESSIONAL USE ONLY

Manufactured in USA of foreign and US components
Auto Magic is a trademark of ITW Evercoat
a division of Illinois Tool Works Inc.
6600 Cornell Rd, Cincinnati, OH 45242
513-489-7600 | AutoMagic.com

ITW Permatex Canada
a division of Illinois Tool Works Inc.
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5

187444 6.2020