# SAFETY DATA SHEET.



Issuing date 11-May-2015

Revision Date 11-May-2015

Version 1.01

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING


<u>Product identifier</u> Product name	SUPER SOLV
Recommended use of the chemical and restrictions on use	
Product code	HT 18007
Product Type Synonyms	Extremely flammable aerosol None
Supplier's details	
Recommended Use Uses advised against	MULTI-PURPOSE SOLVENT. No information available
Manufactured For: Hi-Tech Industries 33106 W. 8 Mile Farmington, MI 48336 Company Telephone: 248-358-2626	
Chemical Emergency Phone Number	INFOTRAC 1-352-323-3500 (International) 1-800-535-5053 (North America)

### 2. HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

# GHS Label elements, including precautionary statements



### **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. — No smoking Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

### **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention Specific treatment (see first aid on this label) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse If skin irritation occurs: Get medical advice/attention IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

### **Precautionary Statements - Storage**

Store locked up Store in a well-ventilated place. Keep container tightly closed Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

None

### Other information

• Toxic to aquatic life with long lasting effects

0% of the mixture consists of ingredient(s) of unknown toxicity

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No	Weight %*
PETROLEUM DISTILLATES	64742-89-8	60-70
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	10-20
XYLENE	1330-20-7	1-10
ETHYL BENZENE	100-41-4	1-10

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

### First aid measures for different exposure routes

Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If irritation persists, call a physician.		
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.		
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately.		
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.		
Most important symptoms/effects, a	acute and delayed		
Main Symptoms	Causes eye and skin irritation. Irritating to respiratory system. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.		
Indication of immediate medical attention and special treatment needed, if necessary			
Notes to physician	Treat symptomatically.		

### **5. FIRE-FIGHTING MEASURES**

### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Decomposition by contact with water may generate vapors which can be ignited by heat or open flame.

### Specific hazards arising from the chemical

No information available.

### Explosion Data

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with eyes,skin, and clothing. Avoid breathing vapors or mists Use with adequate ventilation. Keep container away from heat,flames, and all other sources of ignition.
Environmental precautions	
Environmental precautions	Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains.
Methods and materials for containr	nent and cleaning up
Methods for Containment	Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Stop leak if you can do it without risk.
Methods for cleaning up	After cleaning, flush away traces with water. Clean contaminated surface thoroughly. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges. Prevent product from entering drains.

### 7. HANDLING AND STORAGE

# Precautions for safe handling Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Conditions for safe storage, including any incompatibilities Keep away from open flames, hot surfaces and sources of ignition. Keep container tightly closed in a dry and well-ventilated place. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products None known based on information supplied.

Aerosol Level

### 3

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
PROPANE/ISOBUTANE/N-BUTANE	74-98-6: TWA: 1000 ppm	74-98-6:TWA: 1000 ppm	74-98-6:IDLH: 2100 ppm
68476-86-8	106-97-8: STEL: 1000 ppm	TWA: 1800 mg/m <sup>3</sup>	TWA: 1000 ppm
	75-28-5: STEL: 1000 ppm	(vacated) TWA: 1000 ppm	TWA: 1800 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	106-97-8:TWA: 800 ppm
		106-97-8: (vacated) TWA: 800	TWA: 1900 mg/m <sup>3</sup>
		ppm	75-28-5:TWA: 800 ppm
		(vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 1900 mg/m <sup>3</sup>
XYLENE	STEL: 150 ppm	TWA: 100 ppm	-
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m <sup>3</sup>	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m <sup>3</sup>	
ETHYL BENZENE	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4		TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>
		(vacated) TWA: 435 mg/m <sup>3</sup>	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m <sup>3</sup>
		(vacated) STEL: 545 mg/m <sup>3</sup>	

ACGIH: (American Conference of Governmental Industrial Hygienists) OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

### **Exposure controls**

Engineering Measures	Showers
	Eyewash stations
	Ventilation systems.

### Individual protection measures, such as personal protective equipment

- **Eye/Face Protection** Safety glasses with side-shields.
- Skin and body protection Chemical resistant apron. Protective gloves.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

### **Hygiene measures**

Handle in accordance with good industrial hygiene and safety practice.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical and chemical properties

Physical state	Aerosol
Appearance	Clear
Color	No information available

Odor Odor Threshold Light Vanilla Scent No information available

Property	<u>Values</u>	Remarks • Methods
рН	0	
Melting/freezing point	No information available	
Boiling point/boiling range	No information available	
Flash Point	-97 °C / -143 °F	Based on propellant
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit	No information available	
lower flammability limit	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Specific Gravity	0.730	
Water solubility	Practically insoluble	
Partition coefficient: n-octanol/wat	erNo information available	
Autoignition temperature	No information available	Not applicable
Decomposition temperature	No information available	
Viscosity	No information available	
Explosive properties	No information available	
Other information		

VOC Content(%)

100

### **10. STABILITY AND REACTIVITY**

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### **Conditions to Avoid**

Extremes of temperature and direct sunlight.

### **Incompatible Materials**

None known based on information supplied.

### **Hazardous Decomposition Products**

None known based on information supplied.

## **11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure

### **Product Information**

Inhalation	Vapors may irritate throat and respiratory system. May cause drownsiness and dizziness based on components. May cause irritation of respiratory tract. Avoid breathing vapors or mists.
Eye contact	Irritating to eyes. Avoid contact with eyes.
Skin contact	Irritating to skin. Avoid contact with skin.

```
Ingestion
```

Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

Component Information			
Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
PETROLEUM DISTILLATES 64742-89-8	-	= 3000 mg/kg (Rabbit)	-
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat)4 h
ETHYL BENZENE 100-41-4	-	= 15400 mg/kg (Rabbit)	-

### Information on toxicological effects

Symptoms

Symptoms of overexposure may be headache, tiredness, nausea, and vomiting. Causes respiratory irritation. Causes skin and eye irritation. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Eye damage/irritation	Irritating to sl Irritating to e			
Sensitization	None known.			
Germ Cell Mutagenicity	None known.			
Carcinogenicity	The table bel carcinogen.	ow indicates whether each	n agency has evaluated a l	isted ingredient as a
<b>a</b>	0			
Chemical Name	ACGIH	IARC	NTP	OSHA

Chemical Name	ACGIH	IARC	NTP	OSHA
XYLENE	-	Group 3	-	-
1330-20-7				
ETHYL BENZENE 100-41-4	A3	Group 2B	-	-

<i>ital Industrial Hygienists)</i> ancer) <i>Humans</i> tration) luct does not contain any knowse respiratory irritation. May ca	own or suspected reproductive hazards.
<i>Humans</i> tration) luct does not contain any know	· · ·
<i>Humans</i> tration) luct does not contain any know	
tration) luct does not contain any know	
tration) luct does not contain any know	
tration) luct does not contain any know	1 I
luct does not contain any know	
,	1 I
se respiratory irritation. May ca	ause drowsiness and dizziness
nation available.	
ervous system, Eyes, Respira	atory system, Skin.
al misuse by deliberately conc	centrating and inhaling contents may be harmful or
atal if swallowed and enters ai	airways.
2	al misuse by deliberately con

### Numerical measures of toxicity - Product Information

 Unknown Acute Toxicity
 0% of the mixture consists of ingredient(s) of unknown toxicity

 The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 36212 mg/kg

 ATEmix (dermal)
 11381 mg/kg

 ATEmix (inhalation-dust/mist)
 12.5 mg/l

### **12. ECOLOGICAL INFORMATION**

### Ecotoxicity

iniciouganishis puner aquatic invertebrates	Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
---	---------------	-------------------	------------------	-------------------------------	--

PETROLEUM DISTILLATES       4700 mg/L EC50       -       -       -       -         64742-89-8       Pseudokirchneriella subcapitata 72h       -       -       -       -         PROPANE/ISOBUTANE/N- BUTANE       -       -       -       -       -       -         SUTANE       -       -       -       -       -       -       -       -         SUTANE       -       -       13.1 - 16.5 mg/L LC50       -       0.6 mg/L LC5       -       0.6 mg/L LC5         1330-20-7       Lepomis macrochirus 96h       -       -       0.4 mg/L LC50       -       -	-
subcapitata 72h         subcapitata 72h           PROPANE/ISOBUTANE/N- BUTANE 68476-86-8         -         0.6 mg/L LC50         -	-
PROPANE/ISOBUTANE/N- BUTANE 68476-86-8         -         0.6 mg/L LC5         -	-
BUTANE         BUTANE<	-
68476-86-8         -         13.1 - 16.5 mg/L LC50         -         0.6 mg/L LC5	
XYLENE - 13.1 - 16.5 mg/L LC50 - 0.6 mg/L LC5	
	60 Gammarus
I I I I I I I I I I I I I I I I I I I	h 3.82 mg/L
flow-through 13.5 - 17.3 EC50 wate	er flea 48h
mg/L LC50 Oncorhynchus	
mykiss 96h 2.661 - 4.093	
mg/L LC50 Oncorhynchus	
mykiss 96h static 23.53 -	
29.97 mg/L LC50	
Pimephales promelas 96h	
static 30.26 - 40.75 mg/L	
LC50 Poecilia reticulata 96h	
static 7.711 - 9.591 mg/L	
LC50 Lepomis macrochirus	
96h static 13.4 mg/L LC50	
Pimephales promelas 96h	
flow-through 19 mg/L LC50	
Lepomis macrochirus 96h	
780 mg/L LC50 Cyprinus	
carpio 96h semi-static 780	
mg/L LC50 Cyprinus carpio	
96h	
ETHYL BENZENE 4.6 mg/L EC50 11.0 - 18.0 mg/L LC50 - 1.8 - 2.4 mg/L	EC50 Daphnia
100-41-4 Pseudokirchneriella Oncorhynchus mykiss 96h magn	
subcapitata 72h 438 mg/L static 7.55 - 11 mg/L LC50	
EC50 Pseudokirchneriella Pimephales promelas 96h	
subcapitata 96h 2.6 - 11.3 flow-through 9.1 - 15.6 mg/L	
mg/L EC50 LC50 Pimephales prometas	
Pseudokirchneriella 96h static 32 mg/L LC50	
subcapitata 72h static 1.7 - Lepomis macrochirus 96h	
7.6 mg/L EC50 static 4.2 mg/L LC50	
Pseudokirchneriella Oncorhynchus mykiss 96h	
subcapitata 96h static semi-static 9.6 mg/L LC50	
Poecilia reticulata 96h static	

# Persistence and degradability No information available.

Bioaccumulation No information available.

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE	2.8
68476-86-8	
XYLENE	3.15
1330-20-7	
ETHYL BENZENE	3.118
100-41-4	

Other adverse effects

No information available

### **13. DISPOSAL CONSIDERATIONS**

### Waste treatment

Waste Disposal Methods	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated packaging	Do not re-use empty containers.

### **14. TRANSPORT INFORMATION**

DOT Ground	CONSUMER COMMODITY ORM-D or LIMITED QUANTITY
ΙΑΤΑ	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.
IMDG	UN1950, AEROSOLS, 2.1, LTD. QTY.

### **15. REGULATORY INFORMATION**

### International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
PETROLEUM DISTILLATES	Х	Х	Х	Not listed	Х	Х	Х	Х
PROPANE/ISOBUTAN E/N-BUTANE	Х	Х	Х	Not listed	Х	Х	Х	Х
XYLENE	Х	Х	Х	Х	Х	Х	Х	Х
ETHYL BENZENE	Х	Х	Х	Х	Х	Х	Х	Х

### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### U.S. Federal Regulations

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
XYLENE - 1330-20-7	1330-20-7	1-10	1.0
ETHYL BENZENE - 100-41-4	100-41-4	1-10	0.1
SARA 311/312 Hazard Categories			
Acute Health Hazard	Yes		
Chronic Health Hazard	Yes		
Fire Hazard	Yes		
Sudden Release of Pressure Hazard	Yes		
Reactive Hazard	no		

### Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			Х
ETHYL BENZENE 100-41-4	1000 lb	X	X	Х

### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
100 lb		RQ 100 lb final RQ
		RQ 45.4 kg final RQ
1000 lb		RQ 1000 lb final RQ
		RQ 454 kg final RQ
	100 lb	100 lb

### U.S. State Regulations

### **California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
ETHYL BENZENE - 100-41-4	Carcinogen
BENZENE - 71-43-2	Carcinogen
	Developmental
	Male Reproductive
TOLUENE - 108-88-3	Developmental
	Female Reproductive

### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
PETROLEUM DISTILLATES 64742-89-8			Х
XYLENE 1330-20-7	X	Х	Х
ETHYL BENZENE 100-41-4	X	Х	Х

EPA Pesticide Registration Number Not applicable

### <u>Canada</u>

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.



16. OTHER INFORMATION							
<u>NFPA</u>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -			

HMIS	Health Hazard 2	Flammability 4	Physical Hazard	1	Personal protection	В
Prepared By	Americar	n Jetway yrtle Street				
		MI 48184				
	Tel.734-7	/21-5930				
Issuing date	11-May-2	2015				
Revision Date	11-May-2	2015				
Revision Note	,					
No information available						
Disclaimer						

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet