



# SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

**Product name:** Isopropanol, Anhydrous

**Issue Date:** 04/27/2015

**Print Date:** 04/28/2015

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

---

## 1. IDENTIFICATION

---

**Product name:** Isopropanol, Anhydrous

**Recommended use of the chemical and restrictions on use**

**Identified uses:** All-purpose solvent. Industrial solvent for cleaner and coating formulations. Chemical additive.

**COMPANY IDENTIFICATION**

THE DOW CHEMICAL COMPANY  
2030 WILLARD H DOW CENTER  
MIDLAND MI 48674-0000  
UNITED STATES

**Customer Information Number:**

800-258-2436  
SDSQuestion@dow.com

**EMERGENCY TELEPHONE NUMBER**

**24-Hour Emergency Contact:** 800-424-9300

**Local Emergency Contact:** 800-424-9300

---

## 2. HAZARDS IDENTIFICATION

---

**Hazard classification**

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Flammable liquids - Category 2

Eye irritation - Category 2A

Specific target organ toxicity - single exposure - Category 3

**Label elements**

**Hazard pictograms**



Signal word: **DANGER!**

**Hazards**

Highly flammable liquid and vapour.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

**Precautionary statements****Prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/ eye protection/ face protection.

**Response**

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/ attention.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

**Storage**

Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

**Disposal**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

no data available

---

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

---

**Synonyms:** propan-2-ol

This product is a substance.

<b>Component</b>	<b>CASRN</b>	<b>Concentration</b>
isopropanol	67-63-0	100.0%

---

## 4. FIRST AID MEASURES

---

### Description of first aid measures

**General advice:** First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

**Skin contact:** Wash off with plenty of water.

**Eye contact:** Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

**Ingestion:** Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

**Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

### Indication of any immediate medical attention and special treatment needed

**Notes to physician:** Maintain adequate ventilation and oxygenation of the patient. Because rapid absorption may occur through the lungs if aspirated and cause systemic effects, the decision of whether to induce vomiting or not should be made by a physician. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Hemodialysis may be of benefit if substantial amounts have been ingested and the patient is showing signs of intoxication. Consider hemodialysis for patients with persistent hypotension or coma unresponsive to standard therapy (isopropanol levels >400 - 500 mg/dl). (Goldfrank 1998, King et al, 1970). No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

---

## 5. FIREFIGHTING MEASURES

---

**Suitable extinguishing media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

**Unsuitable extinguishing media:** Do not use direct water stream. Straight or direct water streams may not be effective to extinguish fire.

### Special hazards arising from the substance or mixture

**Hazardous combustion products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

**Unusual Fire and Explosion Hazards:** Container may vent and/or rupture due to fire. When product is stored in closed containers, a flammable atmosphere can develop. Electrically ground and bond all equipment. Flammable mixtures of this product are readily ignited even by static discharge. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Flammable mixtures may exist within the vapor space of containers at room temperature. Flammable concentrations of vapor can accumulate at temperatures above flash point; see Section 9.

#### **Advice for firefighters**

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Water may not be effective in extinguishing fire. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Eliminate ignition sources. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Use caution and test if material is burning before entering area. Material burns with invisible flame.

**Special protective equipment for firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

---

## **6. ACCIDENTAL RELEASE MEASURES**

---

**Personal precautions, protective equipment and emergency procedures:** Isolate area. Keep unnecessary and unprotected personnel from entering the area. Refer to section 7, Handling, for additional precautionary measures. Keep personnel out of low areas. Keep upwind of spill. Ventilate area of leak or spill. No smoking in area. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Vapor explosion hazard. Keep out of sewers. For large spills, warn public of downwind explosion hazard. Check area with combustible gas detector before reentering area. Ground and bond all containers and handling equipment. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

**Environmental precautions:** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

**Methods and materials for containment and cleaning up:** Contain spilled material if possible. Ground and bond all containers and handling equipment. Pump with explosion-proof equipment. If available, use foam to smother or suppress. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

---

## **7. HANDLING AND STORAGE**

---

**Precautions for safe handling:** Keep away from heat, sparks and flame. Avoid contact with eyes. Avoid breathing vapor. Wash thoroughly after handling. Keep container closed. Use only with adequate ventilation. No smoking, open flames or sources of ignition in handling and storage area. Electrically bond and ground all containers and equipment before transfer or use of material. Use of non-sparking or explosion-proof equipment may be necessary, depending upon the type of operation. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Vapors are heavier than air and may travel a

long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Never use air pressure for transferring product. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

**Conditions for safe storage:** Minimize sources of ignition, such as static build-up, heat, spark or flame. Keep container closed. Flammable mixtures may exist within the vapor space of containers at room temperature.

#### Storage stability

**Shelf life:** Use within 24 Month

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

Exposure limits are listed below, if they exist.

Component	Regulation	Type of listing	Value/Notation
isopropanol	ACGIH	TWA	200 ppm
	ACGIH	STEL	400 ppm
	OSHA Z-1	TWA	980 mg/m3 400 ppm

### Exposure controls

**Engineering controls:** Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

### Individual protection measures

**Eye/face protection:** Use chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

#### Skin protection

**Hand protection:** Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl chloride ("PVC" or "vinyl"). Examples of acceptable glove barrier materials include: Polyvinyl alcohol ("PVA"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Wear clean, body-covering clothing.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. In confined or poorly ventilated areas, use an approved self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

---

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

**Appearance**

Physical state	Liquid.
Color	Colorless
Odor	Alcohols
Odor Threshold	No test data available
pH	No test data available
Melting point/range	Not applicable to liquids
Freezing point	-89 °C ( -128 °F) <i>Literature</i>
Boiling point (760 mmHg)	82 °C ( 180 °F) <i>Literature</i>
Flash point	<b>closed cup</b> 12 °C ( 54 °F) <i>Tag Closed Cup ASTM D56</i>
Evaporation Rate (Butyl Acetate = 1)	2.9 <i>Literature</i>
Flammability (solid, gas)	Flammable liquid
Lower explosion limit	2.0 % vol <i>Literature</i>
Upper explosion limit	12.0 % vol <i>Literature</i>
Vapor Pressure	33 mmHg at 20 °C (68 °F) <i>Literature</i>
Relative Vapor Density (air = 1)	2.1 <i>Literature</i>
Relative Density (water = 1)	0.7855 at 20 °C (68 °F) / 20 °C <i>Literature</i>
Water solubility	100 % at 20 °C (68 °F) <i>Literature</i>
Partition coefficient: n-octanol/water	log Pow: 0.05 <i>Measured</i>
Auto-ignition temperature	399 °C (750 °F) <i>Literature</i>
Decomposition temperature	No test data available
Kinematic Viscosity	No test data available
Explosive properties	Not explosive
Oxidizing properties	No
Liquid Density	0.785 g/cm <sup>3</sup> at 20 °C (68 °F) <i>Literature</i>
Molecular weight	60 g/mol <i>Literature</i>
Molecular formula	(CH <sub>3</sub> ) <sub>2</sub> CHOH

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

---

## 10. STABILITY AND REACTIVITY

---

**Reactivity:** no data available

**Chemical stability:** Thermally stable at typical use temperatures.

**Possibility of hazardous reactions:** Polymerization will not occur.

**Conditions to avoid:** Exposure to elevated temperatures can cause product to decompose. Avoid static discharge.

**Incompatible materials:** Avoid contact with: Aldehydes. Halogenated organics. Halogens. Strong acids. Strong oxidizers.

**Hazardous decomposition products:** Decomposition products depend upon temperature, air supply and the presence of other materials.

---

## 11. TOXICOLOGICAL INFORMATION

---

*Toxicological information on this product or its components appear in this section when such data is available.*

### **Acute toxicity**

#### **Acute oral toxicity**

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. May cause central nervous system depression. May cause nausea and vomiting. Signs and symptoms of excessive exposure may include: Facial flushing. Low blood pressure. Irregular heartbeats.

LD50, Rat, 5,840 mg/kg OECD 401 or equivalent  
Lethal Dose, Humans, 100 ml Estimated.

#### **Acute dermal toxicity**

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

LD50, Rabbit, > 12,800 mg/kg

#### **Acute inhalation toxicity**

With good ventilation, single exposure is not likely to be hazardous. In poorly ventilated areas, vapors or mists may accumulate and cause respiratory irritation. Prolonged excessive exposure may cause adverse effects. Excessive exposure (400 ppm) to isopropanol may cause eye, nose and throat irritation. Incoordination, confusion, hypotension, hypothermia, circulatory collapse, respiratory arrest and death may follow a longer duration or higher levels. Observations in animals include middle ear lining damage upon exposure to vapors of isopropanol. However, the relevance of this to humans is unknown

LC50, Rat, male and female, 6 Hour, vapour, > 10000 ppm

### **Skin corrosion/irritation**

Prolonged exposure not likely to cause significant skin irritation.  
May cause drying and flaking of the skin.

### **Serious eye damage/eye irritation**

May cause pain disproportionate to the level of irritation to eye tissues.  
May cause moderate eye irritation.  
May cause moderate corneal injury.  
Vapor may cause eye irritation experienced as mild discomfort and redness.  
Vapor may cause lacrimation (tears).

**Sensitization**

Did not demonstrate the potential for contact allergy in mice.  
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

May cause drowsiness or dizziness.  
Route of Exposure: Ingestion  
Target Organs: Central nervous system

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

In animals, effects have been reported on the following organs:  
Kidney.  
Liver.  
Kidney effects have been observed in male rats. These effects are believed to be species specific and unlikely to occur in humans.  
Observations in animals include:  
Lethargy.

**Carcinogenicity**

Did not cause cancer in laboratory animals.

**Teratogenicity**

Isopropanol has been toxic to the fetus in laboratory animals at doses toxic to the mother.

**Reproductive toxicity**

In animal studies, did not interfere with reproduction. In animal studies, did not interfere with fertility.

**Mutagenicity**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Aspiration Hazard**

May be harmful if swallowed and enters airways.

---

---

**12. ECOLOGICAL INFORMATION**

---

*Ecotoxicological information on this product or its components appear in this section when such data is available.*

**Toxicity**

**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis  
(LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 9,640 mg/l, OECD Test Guideline 203 or Equivalent

**Acute toxicity to aquatic invertebrates**



LC50, Daphnia magna (Water flea), static test, 24 Hour, > 1,000 mg/l, OECD Test Guideline 202 or Equivalent

**Acute toxicity to algae/aquatic plants**

NOEC, alga Scenedesmus sp., static test, 7 d, Growth inhibition (cell density reduction), 1,800 mg/l

ErC50, alga Scenedesmus sp., static test, 72 Hour, Growth rate inhibition, > 1,000 mg/l

**Chronic aquatic toxicity**

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, 30 mg/l

**Persistence and degradability**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

**Biodegradation:** 95 %

**Exposure time:** 21 d

**Method:** OECD Test Guideline 301E or Equivalent

10-day Window: Pass

**Biodegradation:** 53 %

**Exposure time:** 5 d

**Method:** Other guidelines

**Theoretical Oxygen Demand:** 2.40 mg/mg

**Chemical Oxygen Demand:** 2.09 mg/mg

**Biological oxygen demand (BOD)**

Incubation Time	BOD
5 d	20 - 72 %
20 d	78 - 86 %

**Photodegradation**

**Test Type:** Half-life (indirect photolysis)

**Sensitizer:** OH radicals

**Atmospheric half-life:** 1.472 d

**Method:** Estimated.

**Bioaccumulative potential**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** 0.05 Measured

**Mobility in soil**

Potential for mobility in soil is very high (Koc between 0 and 50).

**Partition coefficient(Koc):** 1.1 Estimated.

---

### 13. DISPOSAL CONSIDERATIONS

---

**Disposal methods:** DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

---

### 14. TRANSPORT INFORMATION

---

**DOT**

<b>Proper shipping name</b>	Isopropyl alcohol
<b>UN number</b>	UN 1219
<b>Class</b>	3
<b>Packing group</b>	II

**Classification for SEA transport (IMO-IMDG):**

<b>Proper shipping name</b>	ISOPROPYL ALCOHOL
<b>UN number</b>	UN 1219
<b>Class</b>	3
<b>Packing group</b>	II
<b>Marine pollutant</b>	No
<b>Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code</b>	Consult IMO regulations before transporting ocean bulk

**Classification for AIR transport (IATA/ICAO):**

<b>Proper shipping name</b>	Isopropyl alcohol
<b>UN number</b>	UN 1219
<b>Class</b>	3
<b>Packing group</b>	II

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

## 15. REGULATORY INFORMATION

---

### OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Fire Hazard  
Acute Health Hazard  
Chronic Health Hazard

### Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

Components	CASRN
isopropanol	67-63-0

### Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

This product contains the following substances which are subject to CERCLA Section 103 reporting requirements and which are listed in 40 CFR 302.4.

### Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

Components	CASRN
isopropanol	67-63-0

### California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

### United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

---

## 16. OTHER INFORMATION

---

### Hazard Rating System

#### NFPA

Health	Fire	Reactivity
2	3	0

### Revision

Identification Number: 101234176 / A001 / Issue Date: 04/27/2015 / Version: 7.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

**Legend**

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
STEL	Short-term exposure limit
TWA	8-hour, time-weighted average

**Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.