

acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte **Vinyl Wrap Ceramic Coating**

version number GHS 1.0.

Date of compilation. 2023-03-14.

SECTION 1: Identification

Product identifier

Trade name Jade Sapphire - PPF & Matte Vinyl Wrap Ceram-

ic Coating

Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses Polymeric automobile paint sealant

Vehicle coating

HS code 3208.90.00.

1.3 Details of the supplier of the safety data sheet

> B&B Blending, LLC 10963 Leroy Drive Northglenn CO 80233 **United States**

telephone

1.800.875.6320, 1.303.289.6320 e-mail: info@bbblending.com

website bbblending.com

e-mail (competent person)

Btirrell@bbblending.com

1.4 **Emergency telephone number**

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500

24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
A.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
A.4S	Skin sensitization	1	Skin Sens. 1	H317
A.6	Carcinogenicity	2	Carc. 2	H351
A.10	Aspiration hazard	1	Asp. Tox. 1	H304
B.6	Flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources. The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Signal word Danger

Page 1/17 **United States**



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte Vinyl Wrap Ceramic Coating

version number GHS 1.0. Date of compilation. 2023-03-14.

Pictograms

GHS02, GHS07,

GHS08



Hazard statements

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H351 Suspected of causing cancer.

Precautionary statements

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of water.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with wa-

ter/shower.

P308+P313 If exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazardous ingredients for labelling Parachlorobenzotrifluoride

Distillates (petroleum) hydrotreated, light

Solvent naphtha(petroleum), heavy aromatic, Naph-

thalene Depleted

2.3 Other hazards

Hazards not otherwise classified

May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).

May be harmful if inhaled (GHS category 5: acutely toxic - inhalation).

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Contains a PBT-substance in a concentration of \geq 0,1%. Contains a vPvB-substance in a concentration of \geq 0,1%.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

United States Page 2 /17



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte Vinyl Wrap Ceramic Coating

version number GHS 1.0.

Date of compilation. 2023-03-14.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture).

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
decamethylcyclopentasilox- ane	CAS No 541-02-6	55 - < 70	Flam. Liq. 4 / H227 HNOC002 HNOC003 HNOC008	PBT vPvB
distillates (petroleum) hydro- treated, light	CAS No 64742-47-8	12-<20	Asp. Tox. 1 / H304 HNOC011	
parachlorobenzotrifluoride	CAS No 98-56-6	3-<12	Skin Sens. 1B / H317 Carc. 2 / H351 Flam. Liq. 3 / H226 HNOC002 HNOC008	IARC: 2B
Cyclosilazanes, di-Me, Me Hydrogen, polymers with di- Me, Me hydrogen silazanes, and 2,4-TDI	CAS No 2649792-57-2	3-<12	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Flam. Liq. 2 / H225 HNOC010	

Notes

IARC: IARC group 2B: possibly carcinogenic to humans (International Agency for Research on Cancer)

2B:

PBT: The substance was identified as a PBT (persistent, bioaccumulative and toxic) vPvB: The substance was identified as a vPvB (very persistent and very bioaccumulative)

For full text of abbreviations: see SECTION 16.

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

United States Page 3 /17



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte Vinyl Wrap Ceramic Coating

version number GHS 1.0.

Date of compilation. 2023-03-14.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray. BC-powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Water jet.

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NOx). Carbon monoxide (CO). Carbon dioxide (CO2).

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). collect spillage sawdust

kieselgur (diatomite)

sand

universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal.

United States Page 4/17



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte Vinyl Wrap Ceramic Coating

version number GHS 1.0.

Date of compilation. 2023-03-14.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

General rule

Do not use for squirting or spraying.

Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

this information is not available

United States Page 5 /17



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte Vinyl Wrap Ceramic Coating

version number GHS 1.0.

Date of compilation. 2023-03-14.

Relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time
decamethylcyclo- pentasiloxane	541-02-6	DNEL	97.3 mg/m ³	human, inhalatory	worker (industry)	acute - systemic ef- fects
decamethylcyclo- pentasiloxane	541-02-6	DNEL	24.2 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
decamethylcyclo- pentasiloxane	541-02-6	DNEL	97.3 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
decamethylcyclo- pentasiloxane	541-02-6	DNEL	24.2 mg/m ³	human, inhalatory	worker (industry)	chronic - local ef- fects
parachlorobenzotriflu- oride	98-56-6	DNEL	1.025 mg/ m ³	human, inhalatory	worker (industry)	chronic - systemic effects
parachlorobenzotriflu- oride	98-56-6	DNEL	0.4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
parachlorobenzotriflu- oride	98-56-6	DNEL	17.6 μg/cm ²	human, dermal	worker (industry)	acute - local effects

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
decamethylcyclo- pentasiloxane	541-02-6	PNEC	10 ^{mg} / _l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	11 ^{mg} / _{kg}	benthic organisms	sediment	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	13 ^{mg} / _{kg}	(top) predators	water	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	1.1 ^{mg} / _{kg}	pelagic organisms	sediment	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	1.2 ^{µg} / _I	aquatic organisms	freshwater	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	0.12 ^{µg} / _I	aquatic organisms	marine water	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	10 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	11 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	1.1 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	2.54 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
parachlorobenzotriflu- oride	98-56-6	PNEC	2 ^{µg} / _l	aquatic organisms	freshwater	short-term (single instance)
parachlorobenzotriflu- oride	98-56-6	PNEC	0.2 ^{µg} / _l	aquatic organisms	marine water	short-term (single instance)

United States Page 6 /17



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte Vinyl Wrap Ceramic Coating

version number GHS 1.0.

Date of compilation. 2023-03-14.

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
parachlorobenzotriflu- oride	98-56-6	PNEC	0.032 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
parachlorobenzotriflu- oride	98-56-6	PNEC	0.022 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
parachlorobenzotriflu- oride	98-56-6	PNEC	0.002 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
parachlorobenzotriflu- oride	98-56-6	PNEC	0.026 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties Appearance

Physical state	Liquid
Color	Transparent - Light red
Particle	Not relevant Liquid
Odor	Characteristic

United States Page 7 /17



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte Vinyl Wrap Ceramic Coating

version number GHS 1.0.

Date of compilation. 2023-03-14.

The short parameters				
PH (value)	Not determined			
Melting point/freezing point	Not determined			
Initial boiling point and boiling range	>65 °C at 1 atm			
Flash point	58 °C at 101.3 kPa			
Evaporation rate	Not determined			
Flammability (solid, gas)	Not relevant Fluid			

Explosive limits

Lower explosion limit (LEL)	0.6 vol%
Upper explosion limit (UEL)	4.9 vol%
Vapor pressure	33.2 Pa at 25 °C
Density	7.92 ^{lb} / _{gal} at 77 °F 0.95 ^g / _{cm³} at 25 °C
Vapor density	This information is not available
Solubility(ies)	Not determined

Partition coefficient

- n-octanol/water (log KOW)	This information is not available
Auto-ignition temperature	262 °C Auto-ignition temperature (liquids and gases)
Viscosity	Not determined
Explosive properties	None
Oxidizing properties	None

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2B Maximum permissible surface temperature on the equipment: 260°C
	1

United States Page 8 /17



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte Vinyl Wrap Ceramic Coating

version number GHS 1.0.

Date of compilation. 2023-03-14.

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated

Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful in contact with skin or if inhaled.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI	2649792-57-2	oral	500 ^{mg} / _{kg}

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

United States Page 9 /17



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte Vinyl Wrap Ceramic Coating

version number GHS 1.0.

Date of compilation. 2023-03-14.

Carcinogenicity

Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
parachlorobenzotrifluoride	98-56-6	2B	

Legend

2B Possibly carcinogenic to humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
decamethylcyclopentas- iloxane	541-02-6	LC50	>16 ^{µg} / _I	fish	96 h
decamethylcyclopentas- iloxane	541-02-6	EC50	>2.9 ^{µg} / _I	aquatic invertebrates	48 h
parachlorobenzotrifluor- ide	98-56-6	LC50	3 ^{mg} / _l	fish	48 h
parachlorobenzotrifluor- ide	98-56-6	ErC50	>0.41 ^{mg} / _l	algae	72 h
parachlorobenzotrifluor- ide	98-56-6	EC50	>0.41 ^{mg} / _l	algae	72 h

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
decamethylcyclopentas- iloxane	541-02-6	LC50	>16 ^{µg} / _I	fish	14 d
decamethylcyclopentas- iloxane	541-02-6	EC50	>15 ^{µg} / _I	aquatic invertebrates	21 d
parachlorobenzotrifluor- ide	98-56-6	LC50	6.5 ^{mg} / _l	fish	24 h

United States Page 10 /17



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte **Vinyl Wrap Ceramic Coating**

version number GHS 1.0.

Date of compilation. 2023-03-14.

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
parachlorobenzotrifluor- ide	98-56-6	EC50	242.1 ^{mg} / _I	microorganisms	30 min

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

The substance fulfills the very bioaccumulative criterion.

Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Contains a PBT-substance in a concentration of \geq 0,1%. Contains a vPvB-substance in a concentration of \geq 0,1%.

Endocrine disrupting properties 12.6

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	1993
	DOT	UN 1002
	IMDG-Code	1993 UN
	ICAO-TI	1993 UN 1993

UN proper shipping name 14.2

Flammable liquid, n.o.s. DOT Flammable liquid, n.o.s. **IMDG-Code** FLAMMABLE LIQUID, N.O.S. **ICAO-TI** Flammable liquid, n.o.s.

Page 11 /17 **United States**



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte Vinyl Wrap Ceramic Coating

version number GHS 1.0. Date of compilation. 2023-03-14.

Technical nameHazardous ingredients Parachlorobenzotrifluoride

Cyclosilazanes, di-Me, Me Hydrogen, polymers with

di-Me, Me hydrogen silazanes, and 2,4-TDI

14.3 Transport hazard class(es)

DOT 3
IMDG-Code 3
ICAO-TI 3

14.4 Packing group III Substance presenting low danger

DOT III
IMDG-Code III
ICAO-TI III

14.5 Environmental hazards Hazardous to the aquatic environment

Environmentally hazardous substance (aquatic Decamethylcyclopentasiloxane **environment)**

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)Additional information

Particulars in the shipper's declaration

UN1993, Flammable liquid, n.o.s., (contains: parachlorobenzotrifluoride, Cyclosilazanes, di-Me, Me, Hy

chlorobenzotrifluoride, Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI), 3, III, environmentally hazardous

Danger label(s)

Fish and tree



Environmental hazards Yes

Hazardous to the aquatic environment

Special provisions (SP)
B1, B52, IB3, T4, TP1, TP29

ERG No 128

International Maritime Dangerous Goods Code (IMDG)Additional information

Marine pollutant Yes

Hazardous to the aquatic environment

Decamethylcyclopentasiloxane

Danger label(s) 3
Fish and tree



Special provisions (SP) 223, 274, 955

Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L
EmS F-E, S-E
Stowage category A

United States Page 12 /17



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte Vinyl Wrap Ceramic Coating

version number GHS 1.0. Date of compilation. 2023-03-14.

International Civil Aviation Organization (ICAO-IATA/DGR)Additional information

Environmental hazards Yes

Hazardous to the aquatic environment

Danger label(s) 3



Special provisions (SP)

Excepted quantities (EQ)

Limited quantities (LQ)

A3

E1

10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
decamethylcyclopentasiloxane	541-02-6	solvents	Canada PBiTs CECBP - Priority Chemicals EC PBTs
distillates (petroleum) hydrotreated, light	64742-47-8	solvents	
parachlorobenzotrifluoride	98-56-6	solvents	
Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI	2649792-57-2	refractory resin	
polydimethylsiloxane	63148-62-9	surface modifier	
polytrimethylhydrosilylsiloxane	68988-56-7	surface modifier	
trimethylsiloxysilicate	68988-56-7	resin	
7-(diethylamino)-4-methyl-2H-chromen-2-one	91-44-1	colorant	
tetra(trimethylsiloxy)silane	3555-47-3	surface modifier	Canada PBiTs

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals				
Name acc. to inventory	CAS No	Wt%	Remarks	Type of the toxicity
naphthalene	91-20-3	0.000011		cancer
p-chloro-α,α,α-trifluorotoluene (para-Chloroben- zotrifluoride, PCBTF)	98-56-6	7.448		cancer

United States Page 13/17



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte Vinyl Wrap Ceramic Coating

version number GHS 1.0.

Date of compilation. 2023-03-14.

VOC content

Regulated Volatile Organic Compounds (VOC-EPA) 0.002189 % Regulated Volatile Organic Compounds (VOC-Cal ARB) 0.002189 %

Industry or sector specific available guidance(s) NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperat- ures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperat- ures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	not all ingredients are listed
AU	AIIC	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed

United States Page 14 /17



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte Vinyl Wrap Ceramic Coating

version number GHS 1.0.

Date of compilation. 2023-03-14.

Country	Inventory	Status
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed

Legend

AllC Australian Inventory of Industrial Chemicals CICR Chemical Inventory and Control Regulation

CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)

DSL Domestic Substances List (DSL)

ECSI EC Substance Inventory (EINECS, ELINCS, NLP)

IECSC Inventory of Existing Chemical Substances Produced or Imported in China

INSQ National Inventory of Chemical Substances

ISHA-ENCS Inventory of Existing and New Chemical Substances (ISHA-ENCS)

KECI Korea Existing Chemicals Inventory
NDSL Non-domestic Substances List (NDSL)
NZIOC New Zealand Inventory of Chemicals

PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)

REACH Reg. REACH registered substances
TCSI Taiwan Chemical Substance Inventory

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Alignment to regulation. Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: section 9, section 14

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
49 CFR US DOT	49 CFR U.S. Department of Transportation
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal ARB	California Air Resources Board
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances

United States Page 15 /17



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte Vinyl Wrap Ceramic Coating

version number GHS 1.0.

Date of compilation. 2023-03-14.

Abbr.	Descriptions of used abbreviations
EmS	Emergency Schedule
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture.

Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

United States Page 16 /17



acc. to 29 CFR 1910.1200 App D

Jade Sapphire - PPF & Matte Vinyl Wrap Ceramic Coating

version number GHS 1.0.

Date of compilation. 2023-03-14.

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States Page 17 /17